

[→ Product Website](#)[→ Experience in AR](#)

The all-round monitor for the office. The monitor's viewing angle, contrast ratio and brightness help deliver superb ergonomics for everyday use in the office. The clear display with an aspect ratio of 16:10 and a resolution of 1920 x 1200 pixels boosts work productivity. Visual elements and colours are displayed crisply and clearly. The EV2360's optional Auto EcoView function automatically adjusts the screen's brightness. This reduces energy consumption and lowers CO2 emissions from power generation. As an added bonus, having the right brightness levels helps prevent distracting glare. This way, both the user and the environment benefit. The EV2360 is targeted at companies, government agencies and home users who are looking for a high-quality monitor.

- ✓ 22.5" LCD monitor with a 16:10 aspect ratio and IPS technology for outstanding image quality
- ✓ Bezel only 1 mm: amazingly compact and ultra-elegant design
- ✓ Flicker-free image reproduction thanks to hybrid brightness control
- ✓ Auto EcoView and EcoView Optimizer deliver maximum power savings and superb ergonomics
- ✓ Optimised antireflection properties and flexible positioning
- ✓ USB 3.1 hub with one upstream and two downstream ports
- ✓ DisplayPort, HDMI and D-sub signal inputs
- ✓ Proven to be environmentally friendly and produced in a socially responsible way
- ✓ 5-year warranty for highest investment security

Technical Data

GENERAL		FEATURES & OPERATION	
Item no.	EV2360-BK EV2360-WT	Preset color/greyscale modes	2x manual memory locations, sRGB, Paper, Movie, DICOM
Case color	Black White	DICOM tone curve	✓
Areas of application	Office	Auto EcoView	✓
Product line	FlexScan	EcoView Index	✓
Areas of application	Large and medium-sized companies, Private user & small business, Finance	EcoView Optimizer	✓
Specific system requirements	None, compatible with most computers and operating systems including macOS and Windows	Overdrive	✓
EAN	4995047055198 4995047055204	No flickering	✓
		HDCP Decoder	✓
		Automatic signal input recognition	✓
		Built-in speakers	✓
		On-screen menu languages	de, en, fr, es, it, se
		Adjustment options	Color Mode, Brightness, Contrast, Color temperature /White point, Gamma, Overdrive, Colour tone, Color saturation, Resolution, Scaling, OSD language, Signal input, All EcoView functions, Volume
		Button Guide	✓
		Integrated power unit	✓
SCREEN		ELECTRICAL DATA	
Screen size [in inches]	22.5	Frequency	Display Port: 31-75.5 kHz/59-61 Hz; HDMI: 15-75.5 kHz/49-61 Hz, 59-61 Hz; D-Sub: 31-75.5 kHz/59-61 Hz
Screen size [in cm]	57.2	Power consumption (typical) [in watts]	11
Format	16:10	Maximum Power Consumption [in watts]	37 (at maximum brightness with all signal inputs and USB ports in use)
Viewable image size (width x height) [in mm]	488.2 x 297.2	Max. Power consumption in stand-by mode [in watts]	0.5
Ideal and recommended resolution	1920 x 1200	Power consumption with power switch off [in watts]	0
Pixel pitch [in mm]	0.254 x 0.254	Energy efficiency class	C
Pixel density [in ppi]	101	Energy consumption/1000h [in kWh]	11
Supported resolutions	1920 x 1200, 1920 x 1080 (Full HD), 1680 x 1050, 1280 x 1024, 1024 x 768, 800 x 600, 720 x 400, 640 x 480	Power supply	AC 100-120 V / 200-240 V, 50/60 Hz
Panel technology	IPS	Power management	✓
Max. viewing angle horizontal	178	DIMENSIONS & WEIGHT	
Max. viewing angle vertical	178	Dimensions (incl. stand) (width x height x depth) [in mm]	499 x 334-474 x 233
Number of colors or greyscale	16.7 million colors (D-Sub, 8 Bit), 16.7 million colors (DVI, 8 Bit), 16.7 million colors (DisplayPort, 8 Bit), 16.7 million colors (HDMI, 8 Bit)	Weight (incl. stand) [in kg]	5.5
Color palette/look-up table	1.06 billion color tones / 10 Bit	Dimensions (without stand) (width x height x depth) [in mm]	499 x 321 x 54
Max. color space (typical)	sRGB (100%)	Weight (without stand) [in kg]	3.4
Max. brightness (typical) [in cd/m ²]	250	Dimension drawing (PDF)	Dimension drawing (PDF)
Max. dark room contrast (typical)	1000:1	Rotatability of the stand [in °]	344
Response time grey-grey alternation (typical) [in ms]	5	Tiltability forwards/backwards [in °]	5 / 35
Backlight	LED	Pivot between portrait / landscape	clockwise and anti-clockwise
CONNECTIONS		Height adjustment range [in mm]	140
Signal inputs	D-Sub, DisplayPort (HDCP 1.3), HDMI (HDCP 1.4)	Hole spacing	100 x 100
USB specification	USB 5Gbps (USB 3)		
USB upstream ports	1 x type B		
USB downstream ports	2x type A		
Graphic signal	RGB Analog, DisplayPort, HDMI (RGB, YUV)		
Sync formats	Separate		
Audio input	3.5 mm stereo jack, DisplayPort, HDMI		
Audio / headphone output	3.5 mm stereo jack		

CERTIFICATION & STANDARDS

Certification	CE, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), TCO Certified Generation 9, EPEAT 2018 (US), TÜV/Blue Low Light Content, TÜV/Flicker Free, RCM, cTÜVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA ENERGY STAR, RoHS, WEEE, China RoHS, CCC, BIS, BSMI, EAC
---------------	--

SOFTWARE & ACCESSORIES

Accompanying software and other accessories are available for download	Screen InStyle
Other box contents	USB cable (Type A - Type B), Signal cable DisplayPort - DisplayPort, Manual via download, Power cord, Quick guide
Accessories	PM200-K, CP200, HH200PR-K, PCSK-03

WARRANTY

Warranty periode	5 years for unit and LCD module up to 30,000 operating hours, whichever comes first.
Included warranty	Zero pixel defects guarantee; no fully illuminated sub-pixels (sub-pixels ISO 9241-307) for six months from date of purchase.



**Experience the
EV2360 in AR now!**