



[→ Product Website](#)

The perfect all-rounder for the office. The FlexScan EV2430-BK is your ideal assistant in the office for everyday work. This handy all-rounder features power managing functionality and an ergonomic design and it's easy on your eyes for long days in the office. It features three signal ports to connect to computers. In addition, there is a USB hub and headphone/audio jacks that are situated on the side of the monitor. Modern IPS technology enables the FlexScan EV2430-BK to offer horizontal and vertical viewing angles of 178°. Auto EcoView, the brightness sensor, prevents disruptive glaring and reduces strain on the eyes. It also detects changes in the ambient light, automatically adjusting the screen brightness throughout the course of the day.

- ✓ A 24-inch LCD monitor with 16:10 aspect ratio and LED technology in an ergonomic, space-saving design
- ✓ Contrast 1000:1, brightness 300 cd/m<sup>2</sup>
- ✓ Auto EcoView, EcoView Index, EcoView Sense, and EcoView Optimizer for maximum power savings and superb ergonomics
- ✓ Integrated speakers and headphone jack
- ✓ USB hub with one upstream and two downstream ports
- ✓ DisplayPort, DVI-D, and D-sub ports for digital and analogue connections

## Technical Data

### GENERAL

Item no.	EV2430-BK EV2430-GY
Case color	Black Light gray
Areas of application	Office
Product line	FlexScan
Areas of application	Large and medium-sized companies, Private user & small business, Finance
EAN	4995047052999 4995047052982

### SCREEN

Screen size [in inches]	24.1
Screen size [in cm]	61.1
Format	16:10
Viewable image size (width x height) [in mm]	518 x 324
Ideal and recommended resolution	1920 x 1200
Pixel pitch [in mm]	0.27 x 0.27
Pixel density [in ppi]	94
Supported resolutions	1920 x 1200, 1680 x 1050, 1600 x 1200, 1280 x 1024, 1024 x 768, 800 x 600, 720 x 400, 640 x 480
Panel technology	IPS
Max. viewing angle horizontal	178
Max. viewing angle vertical	178
Number of colors or greyscale	16.7 million colors (D-Sub, 8 Bit), 16.7 million colors (DVI, 8 Bit), 16.7 million colors (DisplayPort, 8 Bit)
Color palette/look-up table	1.06 billion color tones / 10 Bit
Max. color space (typical)	sRGB (100%)
Max. brightness (typical) [in cd/m <sup>2</sup> ]	300
Max. dark room contrast (typical)	1000:1
Response time grey-grey alternation (typical) [in ms]	14
Max. refresh rate [in Hz]	60
Backlight	LED

### CONNECTIONS

Signal inputs	D-Sub, DisplayPort (HDCP 1.3), DVI-D (HDCP 1.4)
USB specification	USB 2
USB upstream ports	1 x type B
USB downstream ports	2x type A
Graphic signal	DVI Single Link (TMDS), RGB Analog, DisplayPort
Sync formats	Separate
Audio input	3.5 mm stereo jack, DisplayPort
Audio / headphone output	3.5 mm stereo jack

### FEATURES & OPERATION

Preset color/greyscale modes	2x manual memory locations, sRGB, Paper, Movie
Auto EcoView	✓
EcoView Index	✓
EcoView Optimizer	✓
No flickering	✓
HDCP Decoder	✓
Automatic signal input recognition	✓
Built-in speakers	✓
On-screen menu languages	de, en, fr, es, it, se
Adjustment options	Color Mode, Brightness, Contrast, Color temperature /White point, Gamma, Colour tone, Color saturation, Resolution, Scaling, OSD language, Signal input, All EcoView functions, Volume
Integrated power unit	✓

### ELECTRICAL DATA

Frequency	Display Port: 31-76 kHz/59-61 Hz; DVI-D: 31-76 kHz/59-61 Hz; D-Sub: 31-76 kHz/55-61 Hz;
Power consumption (typical) [in watts]	12
Maximum Power Consumption [in watts]	36 (at maximum brightness with all signal inputs and USB ports in use)
Max. Power consumption in stand-by mode [in watts]	0.3
Power consumption with power switch off [in watts]	0
Energy efficiency class	E
Energy consumption/1000h [in kWh]	15
Power supply	AC 100-120 V / 200-240 V, 50/60 Hz

### DIMENSIONS & WEIGHT

Dimensions (incl. stand) (width x height x depth) [in mm]	553 x 368-499 x 233
Weight (incl. stand) [in kg]	6.7
Dimensions (without stand) (width x height x depth) [in mm]	553 x 358 x 57
Weight (without stand) [in kg]	4.3
Dimension drawing (PDF)	<a href="#">Dimension drawing (PDF)</a>
Rotatability of the stand	344
Tiltability	5 / 35
Pivot between portrait / landscape	90° (clockwise)
Height adjustment range [in mm]	140
Hole spacing	100 x 100

### CERTIFICATION & STANDARDS

Certification	CE, UKCA, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), TCO Certified Generation 8, EPEAT 2018 (US), TÜV/Blue Low Light Content, TÜV/Flicker Free, RCM, cTÜVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA ENERGY STAR, RoHS, WEEE, China RoHS, CCC
---------------	--

## SOFTWARE & ACCESSORIES

---

<b>Other box contents</b>	Signal cable DVI-D - DVI-D, Signal cable DisplayPort - DisplayPort, Power cord, Quick guide
<b>Accessories</b>	PM200-K

---

## WARRANTY

---

<b>Warranty periode</b>	5 years for unit and LCD module up to 30,000 operating hours, whichever comes first.
<b>Included warranty</b>	Zero pixel defects guarantee; no fully illuminated sub-pixels (sub-pixels ISO 9241-307) for six months from date of purchase.

---