





Product Website

The EV2460 immediately stands out thanks to its extremely narrow bezel. The compact and attractive design provides more desk space. In terms of picture quality and ergonomics, the 23.8-inch monitor in 16:9 aspect ratio also meets the highest demands for a modern screen. An anti-reflection coating and Auto EcoView ensure a glare-free view of the screen. The LCD panel featuring IPS technology enables the greatest possible viewing angles, making it a pleasure to work with the EV2460. The monitor is virtually frameless and is especially impressive when used for multimonitor viewing. It offers a wide range of connection options thanks to DisplayPort, HDMI, DVI-D and D-sub input as well as four USB downstream ports.

- 23.8-inch LCD monitor in 16:9 aspect ratio featuring IPS technology for excellent image quality
- Bezel only 1 mm: amazingly compact and ultra-elegant design
- Flicker-free image reproduction thanks to hybrid brightness control
- Auto EcoView and EcoView Optimizer for maximum energy-efficiency and superb ergonomics
- Optimised antireflection properties and flexible positioning
- USB 3.1 hub with one upstream and four downstream ports
- OisplayPort, HDMI, DVI-D and D-sub signal inputs
- Proven to be environmentally friendly and produced in a socially responsible way
- 5-year warranty for highest investment security




Design

A pleasing sight on any desk

Elegant design

The monitor's appearance can be the key to creating a pleasant working atmosphere. Whether you are at home or in the office, the monitor's virtually frameless design and ergonomic functionality allows it to fit naturally into your workplace environment. The housing is available in both an elegant black and in white, with matching white cables.



Controls integrated into bezel

Electrostatic switches are integrated into the front of the EV2460 instead of mechanical buttons. This ensures ease of use while also giving the monitor an extremely elegant look. The speakers and all the controls are also built into the bezel, pointing forward in the direction of the user. They are fully integrated into the monitor's flat, nearly frameless design to offer an excellent user experience.





Image quality Precise, high-contrast, bright and crisp screen

Maximum image quality thanks to the IPS panel

The monitor is capable of all three key elements of excellent image quality: excellent resolution of 1920 x 1080 (Full HD) pixels, maximum contrast of 1000:1, and stable brightness of up to 250 cd/m². That means you will experience razor-sharp text contours, brilliant graphics, and clear images. Thanks to the high-quality IPS panels with LED backlight, contrasts and colours remain stable from every viewing angle.






Precise color control

An image can only be perfect if the colours are, too. This is why EIZO monitors have a 10-bit look-up table at a minimum, which allows the colour information to be assigned much more precisely than with conventional 8-bit LUTs. The finest colour gradations ensure that gradients are always perfectly displayed, while also offering customised adjustment options. For example, you can adjust the white balance from 4000 K to 10 000 K in 500-K intervals.







Look-Up-Table with 8 bit

Overdrive to quickly change images

Fast, faster, overdrive. The overdrive function accelerates switching time so that the gray-gray change takes only 5 ms on average. You can watch films and rapidly changing images without annoying afterglow.

ErgonomicsWorking in a relaxed manner

Save electricity and your eyes with Auto EcoView

At day, at night, bright, dark: No matter when and how you work, the Auto EcoView function continuously measures changes of the ambient light and optimises the monitor with ideal brightness values automatically by using a sensor. The benefits: Annoying glare is reduced, your eyes will not get tired as quickly. A special two-point control takes into account the brightest and darkest environment over the course of the day with the respectively desired screen brightness. Another advantage: Thanks to the automatic brightness adjustment, you will save up to 50% of your electricity costs in comparison to a monitor that is permanently operated at maximum brightness.

Of course, you can also continue to configure the monitor manually. EcoView Index is used for orientation on how environmentally friendly and economical your settings are.



During the day



In the evening

FOR THE SAKE OF THE EYES


Flicker free

To help protect your eyes, EIZO has developed a hybrid technology to control the backlight. This combines the benefits of the otherwise standard PWM (pulse width modulation) and DC (direct current) control. The PWM control uses much higher frequencies than standard PWM methods. The result: a flicker-free viewing experience while maintaining picture quality and colour stability. In addition, compared to pure DC control, you can adjust the brightness to less than 1% of the maximum value in darkly lit rooms. The benefit: Your screen remains free from glare even under these conditions.

The flicker-free and low blue light content of the EIZO FlexScan monitors is certified by TÜV Rheinland.

Anti-glare coating: more image, less reflection


The EV2460 offers a perfect, non-glare surface. By minimising glare by diffusing the reflected light, the EV2460 effectively protects your eyes from straining. This keeps your eyes from getting as tired and allows you to sit comfortably in front of the monitor, without having to sit in a forced position to prevent glare.








Ergonomic stand

Ergonomic and stable: the adjustable stand focuses on ergonomics. You can rotate, swivel and tilt the monitor stand until you find the most comfortable setting for your back, neck and sitting posture. It features continuous height adjustment and can be lowered almost to the base plate of the stand, enabling you to position the top image line ergonomically right below your eye level.









Rotation clockwise and anti-clockwise

Variety of ports Best connectivity

One monitor, many ports


It couldn't be easier: Most end devices, such as PC, laptop, mouse, keyboard or headphones, can be connected directly to the monitor, thanks to its wide range of signal interfaces and ports. This makes your daily work easier and ensures a tidy desk.



Software and ease of use Features for greater comfort

Preset color modes: optimized display at the touch of a button


Pre-set color modes optimise the viewing of images, texts or films. Because it makes a difference whether you are watching a film, editing a picture, surfing the net, or writing texts. At the touch of a button, you set the respective pre-set for brightness, gamma correction and colour temperature. For example, the Paper mode simulates the pleasant contrast of printed paper, which is easy on the eyes when reading and prevents fatigue.





Operation made easy thanks to the Button Guide

With the Button Guide, you have all functions at a glance. One touch of the control panel is enough, and the function assignment of the buttons is displayed. Your advantage: clarity of operation and a clean, uncluttered design.



MONITORSTEUERUNG UND ADMINISTRATION

Screen InStyle


In addition to the on-screen menu, you can conveniently control the EV2460 by using the Screen InStyle software on a Windows PC. The configuration options include color reproduction, energy saving options, and ergonomic functions. In multi-screen systems, the settings can be applied synchronously to all connected screens with Screen InStyle.

System administrators can centrally manage and control monitors connected in the network with Screen InStyle installed using the Screen InStyle Server application. This optimises power consumption and simplifies asset management of the monitors.

COMPANY-WIDE DEFAULT SETUP

Monitor Configurator

Workload reduction for administrators: The software allows you to create a default setup for all relevant monitor settings. This setup can be distributed to the connected monitors via the local network which facilitates the roll-out process.



Sustainability

Environmentally and socially conscious production

ECOVIEW OPTIMIZER

Save up to 30% of energy

Save electricity without compromising quality: The Eco-View Optimizer reduces the background lighting fully automatically for dark images. This reduces electricity consumption by up to 30%. At the same time, the signal is amplified and the color tone values adjusted. The result: You will enjoy the image quality you are used to but consume less power.





Zero-watt consumption thanks to the power switch

The monitors have an integrated mechanical power switch, which is extremely practical and energy-saving: If you switch off the monitor using the power switch, the device will stop consuming any power at all. Moreover, it consumes a maximum of 0.5 watt in standby mode.

Socially responsible production

The EV2460 is produced in a socially responsible way. It is free of child labour and forced labour. Suppliers along the supply chain have been carefully selected and they have also committed themselves to produce in a socially responsible way. This applies in particular to conflict minerals. We present a detailed report about our social responsibility annually and voluntarily.



Environmentally and climate friendly

Each EV2460 is manufactured in our own factory, which implements an environmental and energy management system in accordance with ISO 14001 und ISO 50001. This includes measures to reduce waste, wastewater and emissions, resource and energy consumption, as well as to encourage environmentally conscious behavior among employees. We publicly report on these measures on an annual basis.



Sustainable and durable

The EV2460 is designed for a long service life that takes into account the entire lifecycle and impact on the environment. It is generally well above the five-year guarantee. Spare parts are available up to five years after the end of production. The monitor's long service life and the ability to repair it save resources and the climate. When designing the EV2460 we paid attention to reducing resource consumption by using high-quality components and materials and being meticulous in production.





A natural beauty

Reducing the use of volatile organic compounds (VOCs) found in material production, such as some paints, is a global concern.

Through years of research, EIZO has succeeded in achieving a smooth, nearly homogeneous color and texture in its monitor housings without the use of varnish.



Compliance with standards and guidelines

The monitor is certified according to important and allencompassing sustainability standards such as TCO Certified Generation 9, EPEAT and ENERGY STAR. The EV2460 is a safe investment, when taking into account issues such as ESG (Environmental, social and corporate governance) or SDG (Sustainable Development Goals) from the United Nations and following the necessary guidelines.



Warranty

Highest investment security

Five-year warranty

EIZO grants a five-year warranty. This is possible thanks to the highly developed production process based on a simple principle of success: sophisticated and innovative technology, made from high-end materials.







Technical Data

| ^ | - | | - | n | • | ٠ |
|---|---|---|---|---|---|---|
| u | E | N | E | к | А | L |
| | | | | | | |

| GENERAL | |
|---|--|
| Item no. | EV2460-BK EV2460-WT |
| Case color | Black White |
| Areas of application | Office |
| Product line | FlexScan |
| Areas of application | Large and medium-sized companies, Private user ϑ small business, CAD, Finance, Control rooms, Hospital administration |
| EAN | 4995047055297 4995047055303 |
| SCREEN | |
| Screen size [in inches] | 23,8 |
| Screen size [in cm] | 60,5 |
| Format | 16:9 |
| Viewable image size (width x height) [in mm] | 527 x 296,5 |
| Ideal and recommended resolution | 1920 x 1080 (Full HD) |
| Pixel pitch [in mm] | 0,2745 x 0,2745 |
| Pixel density [in ppi] | 93 |
| Supported resolutions | 1920 x 1080 (Full HD), 1680 x 1050, 1280 x 1024, 1024 x 768, 800 x 600, 720 x 400, 640 x 480 |
| Panel technology | IPS |
| Max. viewing angle horizontal | 178 |
| Max. viewing angle vertical | 178 |
| Number of colors or greyscale | 16.7 million colors (D-Sub, 8 Bit), 16.7 million colors (DVI 8 Bit), 16.7 million colors (DisplayPort, 8 Bit), 16.7 million colors (HDMI, 8 Bit) |
| Color palette/look-up table | 1.06 billion color tones / 10 Bit |
| Max. color space (typical) | sRGB (100%) |
| Max. brightness (typical) [in cd/m²] | 250 |
| Max. dark room contrast (typical) | 1000:1 |
| maxi dan i room oomi dot (tgprout) | |
| Response time grey-grey alternation (typical) [in ms] | 5 |

CONNECTIONS

| D-Sub, DisplayPort (HDCP 1.3), HDMI (HDCP 1.4), DVI-D (HDCP 1.4) |
|---|
| USB 5Gbps (USB 3) |
| 1 x type B |
| 4x type A |
| RGB Analog, DisplayPort, HDMI (RGB, YUV), DVI Dual Link (TMDS) |
| Separate |
| 3.5 mm stereo jack, DisplayPort, HDMI |
| 3.5 mm stereo jack |
| |

FEATURES & OPERATION

| Preset color/greyscale modes | 2x manual memory locations, sRGB, Paper, Movie, DICOM |
|------------------------------------|--|
| DICOM tone curve | ✓ |
| Auto EcoView | ✓ |
| EcoView Index | ✓ |
| EcoView Optimizer | ✓ |
| Overdrive | ✓ |
| No flickering | ✓ |
| HDCP Decoder | ✓ |
| Automatic signal input recognition | ✓ |
| Built-in speakers | ✓ |
| On-screen menu languages | de, en, fr, es, it, se |
| Adjustment options | Color Mode, Brightness, Contrast, Color temperature /White point, Gamma, Overdrive, Colour tone, Color saturation, Resolution, Scaling, OSD language, Signal input, All EcoView functions, Volume |
| Button Guide | ✓ |
| Integrated power unit | ✓ |

ELECTRICAL DATA

| ELECTRICAL DATA | |
|--|--|
| Frequency | Display Port: 31-68 kHz/59-61 Hz; HDMI: 49-51 Hz/59-61 Hz; DVI-D: 31-68 kHz/59-61 Hz; D-Sub: 31-68 kHz/59-61 Hz; |
| Power consumption (typical) [in watts] | 10 |
| Maximum Power Consumption [in watts] | 50 (at maximum brightness with all signal inputs and USB ports in use) |
| Max. Power consumption in stand-by mode [in watts] | 0.5 |
| Power consumption with power switch off [in watts] | 0 |
| Energy efficiency class | В |
| Energy consumption/1000h [in kWh] | 9 |
| Power supply | AC 100-120 V / 200-240 V, 50/60 Hz |
| Power management | ✓ |
| | |





DIMENSIONS & WEIGHT

| 538 x 333,6-473,6 x 233 |
|--|
| 5.9 |
| 538 x 320 x 54 |
| 3.8 |
| Dimension drawing (PDF) |
| 344 |
| 5 / 35 |
| clockwise and anti-clockwise |
| 140 |
| 100 x 100 |
| |
| CE, UKCA, CB, C-Tick, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), TCO Certified Generation 9, EPEAT 2018 (US), TÜV/Blue Low Light Content, TÜV /Flicker Free, RCM, cTÜVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA ENERGY STAR, ROHS, WEEE, China ROHS. CCC |
| |

| Accompanying software and other accessories are available for download | Screen InStyle |
|--|---|
| Other box contents | USB cable (Type A - Type B), Signal cable DisplayPort - DisplayPort, Manual via download, Power cord, Quick guide |
| Accessories | PM200-K, CP200, HH200PR-K, PCSK-03R |
| WARRANTY | |

| Warranty periode | 5 years for unit and LCD module up to 30,000 operating hours, whichever comes first. |
|-------------------|--|
| Included warranty | Zero pixel defects guarantee; no fully illuminated sub- pixels (sub-pixels ISO 9241-307) for six months from date of purchase. |

Find your EIZO contact: EIZO Europe GmbH Belgrader Straße 2 41069 Mönchengladbach Phone: +49 2161 8210-0