



[→ Product Website](#)

The FDF2382WT-A offers the highest picture quality in 16:9 format on a diagonal of 23". The impressive viewing angle of the IPS LCD module is particularly striking. The undistorted viewing from all angles is optimal for the widescreen format and touch operation, as all controls and information are equally visible. The FDF2382WT-A recognises up to 10 simultaneous touches and allows smooth and accurate stylus input. It ignores incorrect input, for example, from the palm of the hand.

- ✓ 23" touch monitor with 16:9 format and Full HD resolution
- ✓ Multi-touch operation (for example, zooming, scrolling, rotating, shifting)
- ✓ Smooth and accurate pen input with palm recognition
- ✓ Brightness 260 cd/m², contrast 1000:1
- ✓ IPS LCD module with wide viewing angles
- ✓ Flicker-free image reproduction
- ✓ DisplayPort, HDMI and D-Sub input for digital and analogue connection

Technical Data

GENERAL		FEATURES & OPERATION	
Item no.	FDF2382WT-A	Preset color/greyscale modes	2x manual memory locations, sRGB
Case color	Black	HDCP Decoder	✓
Areas of application	Video surveillance, Industry	Automatic signal input recognition	✓
Product line	DuraVision	Built-in speakers	✓
Areas of application	Touch and video monitors, Automation, Video surveillance, Large and medium-sized companies, Private user & small business, Control rooms	On-screen menu languages	de, en, fr, es, it, se
EAN	4995047063216	Adjustment options	Color Mode, Brightness, Contrast, Color temperature /White point, Gamma, Overdrive, Colour tone, Color saturation, Resolution, Scaling, Touch function On/Off, OSD language, Signal input, Volume, Key lock
SCREEN		Integrated power unit	✓
Screen size [in inches]	23	Touchscreen	✓
Screen size [in cm]	58	Touch panel type	Projected capacitive (PCAP)
Format	16:9	Touch compatible OS	Windows 8.1 (64-bit/32-bit), Windows 11, Windows 10
Viewable image size (width x height) [in mm]	509,2 x 286,4	Touch points	10
Ideal and recommended resolution	1920 x 1080 (Full HD)	ELECTRICAL DATA	
Pixel pitch [in mm]	0,265 x 0,265	Frequency	D-Sub: 31-81 kHz/55-76 Hz; Display Port: 31-68 kHz/59-61 Hz; HDMI: 31-68 kHz/59-61 Hz
Supported resolutions	1920 x 1080 (Full HD), 1680 x 1050, 1280 x 1024, 1024 x 768, 800 x 600, 720 x 400, 640 x 480	Power consumption (typical) [in watts]	12
Panel technology	IPS	Maximum Power Consumption [in watts]	47 (at maximum brightness with all signal inputs and USB ports in use)
Max. viewing angle horizontal	178	Max. Power consumption in stand-by mode [in watts]	0.5
Max. viewing angle vertical	178	Power consumption with power switch off [in watts]	0
Number of colors or greyscale	16.7 million colors (D-Sub, 8 Bit), 16.7 million colors (DisplayPort, 8 Bit), 16.7 million colors (HDMI, 8 Bit)	Energy efficiency class	E
Color palette/look-up table	1.06 billion color tones / 10 Bit	Energy consumption/1000h [in kWh]	17
Max. color space (typical)	sRGB (100%)	Power supply	AC 100-240V, 50/60Hz
Max. brightness (typical) [in cd/m ²]	260	DIMENSIONS & WEIGHT	
Max. dark room contrast (typical)	1000:1	Dimensions (incl. stand) (width x height x depth) [in mm]	556,7 x 144,9-353,9 x 216,3-401,3
Response time grey-grey alternation (typical) [in ms]	11	Weight (incl. stand) [in kg]	6.6
Max. refresh rate [in Hz]	60	Dimensions (without stand) (width x height x depth) [in mm]	556,7 x 339,2 x 54
Backlight	LED	Weight (without stand) [in kg]	6
CONNECTIONS		Dimension drawing (PDF)	Dimension drawing (PDF)
Touch port	USB	Tiltability forwards/backwards [in °]	15 / 70
Signal inputs	D-Sub, DisplayPort (HDCP 1.3), HDMI (HDCP 1.4)	Hole spacing	100 x 100
USB specification	USB 5Gbps (USB 3)	CERTIFICATION & STANDARDS	
USB upstream ports	1 x type B	Operating temperature	5 - 35 °C / 20 - 80 % (R.H., non condensing)
USB downstream ports	2x type A	Certification	CE, UKCA, CB, RCM, cTÜVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, RoHS, WEEE, China RoHS, CCC
Graphic signal	RGB Analog, DisplayPort, HDMI (RGB, YUV)	SOFTWARE & ACCESSORIES	
Control port	USB-Protocol	Other box contents	Signal cable HDMI - HDMI, USB cable (Type A - Type B), Signal cable DisplayPort - DisplayPort, Power cord, Quick guide
Sync formats	Separate	Accessories	PM200-K, CP200, PP100-K, TP5
Audio input	3,5 mm stereo jack, DisplayPort, HDMI		
WARRANTY			
Warranty periode	3 years		



DuraVision **FDF2382WT-A**

Find your EIZO contact:
EIZO AG - Switzerland
Moosacherstrasse 6, Au
8820 Wädenswil ZH
Phone +41 44 782 24 40
www.eizo.ch

All product names are trademarks or registered trademarks of EIZO Corporation in Japan and other countries or their respective companies. Copyright © 2024 EIZO Europe GmbH, Belgrader Str. 2, 41069 Mönchengladbach, Germany. All rights, errors and modifications reserved. Latest update: 22.04.2024