



[→ Product Website](#)

The 19-inch FDS1903-A with a traditional 5:4 aspect ratio stands out thanks to its signal inputs designed for video security systems. Its HDMI input supports resolutions up to Full HD. A composite (BNC) input allows analogue video surveillance devices like cameras and recorders to be connected. The FDS1903-A provides support for PAL, SECAM and NTSC signal formats.

- ✓ High image quality for a better view
- ✓ Display with high brightness level
- ✓ Computer and video inputs
- ✓ Support for NTSC/PAL/SECAM
- ✓ Underscan and normal display
- ✓ Two-year guarantee for 24/7 operation

Technical Data

GENERAL

Item no.	FDS1903-ABK FDF1903-AGY
Case color	Black Light gray
Areas of application	Video surveillance, Industry
Product line	DuraVision
Areas of application	Touch and video monitors, Video surveillance
EAN	4995047053965 4995047053958

SCREEN

Screen size [in inches]	19
Screen size [in cm]	48
Format	5:4
Viewable image size (width x height) [in mm]	376 x 301
Ideal and recommended resolution	1280 x 1024
Pixel pitch [in mm]	0,29 x 0,29
Panel technology	TN
Max. viewing angle horizontal	170
Max. viewing angle vertical	160
Number of colors or greyscale	16.7 million colors (BNC, 8 bit), 16.7 million colors (HDMI, 8 Bit)
Max. brightness (typical) [in cd/m ²]	325
Max. dark room contrast (typical)	1000:1
Backlight	LED

FEATURES & OPERATION

24/7 operation	✓
Underscan and normal display	✓
Built-in speakers	✓
On-screen menu languages	de, en
Adjustment options	Signal information, Brightness, Contrast, Color temperature/White point, Colour tone, Color saturation, Viewpoint, Signal input, Volume, Blur reduction
Integrated power unit	✓

CONNECTIONS

Signal inputs	HDMI (HDCP 1.4), BNC
Graphic signal	Composite Video Input, DVI Single Link (TMDS)
Audio input	3,5 mm stereo jack

SOFTWARE & ACCESSORIES

Other box contents	Manual via download
--------------------	---------------------

Find your EIZO contact:
EIZO AG - Switzerland
Moosacherstrasse 6, Au
8820 Wädenswil ZH
Phone +41 44 782 24 40
www.eizo.ch

All product names are trademarks or registered trademarks of EIZO Corporation in Japan and other countries or their respective companies. Copyright © 2024 EIZO Europe GmbH, Belgrader Str. 2, 41069 Mönchengladbach, Germany. All rights, errors and modifications reserved. Latest update: 27.05.2024

ELECTRICAL DATA

Frequency	Digital: 15-68kHz/24-61 Hz
Maximum Power Consumption [in watts]	24
Max. Power consumption in stand-by mode [in watts]	0.4
Power consumption with power switch off [in watts]	0
Energy efficiency class	E
Energy consumption/1000h [in kWh]	15
Power supply	AC 100-240V, 50/60Hz
Power management	✓

DIMENSIONS & WEIGHT

Dimensions (incl. stand) (width x height x depth) [in mm]	405 x 407 - 507 x 205
Weight (without stand) [in kg]	5.9
Dimension drawing (PDF)	Dimension drawing (PDF)
Tiltability forwards/backwards [in °]	0 / 0
Hole spacing	100 x 100

CERTIFICATION & STANDARDS

Operating temperature	0 - 35 °C / 20 - 80 % (R.H., non condensing)
Certification	CE, UKCA, CB, cTÜVus, FCC-A, CAN ICES-3 (A), VCCI-A, RoHS, WEEE

WARRANTY

Warranty periode	2 years
------------------	---------