


[→ Product Website](#)
[→ Experience in AR](#)

3-megapixel medical monitor

The 3 megapixel resolution and high brightness of the RadiForce RX370 are perfect for the precise display of radiology images. Greyscale images, especially of thorax and fine structures, as well as colour images from 3D reconstructions and the combination of different imaging techniques, benefit from the high image quality. If desired, the RX370's Hybrid Gamma PXL function automatically selects the luminance characteristics that matches the image. For example, monochrome X-ray images are displayed with DICOM® greyscale characteristics, while the luminance of other images follows a gamma function. The work-and-flow features of the RX370 include the instant backlight booster. This feature temporarily adjusts the brightness of the monitor up to approx. 1100 cd/m² in order for the radiologist to be able to recognise greyscale differentiation. The brightness automatically returns to the original setting after a short time, allowing the screen to be used under typical diagnostic conditions. The RX370's design and technology offer both ergonomic comfort and unparalleled image precision for use in modern radiology. Even the packaging materials used for the RX370 is exemplary. Instead of polystyrene which previous models have used, a padding made of moulded pulp cellulose is within each RX370 box. This is made from recycled cardboard and paper, all helping to reduce EIZO's ecological footprint.

- ✓ Compact and comfortable 3-megapixel colour screen for radiology reporting
- ✓ Clear recognition of structures through high contrast and blur reduction
- ✓ Palette with 543 billion shades for precise colour reproduction with up to 10 bit
- ✓ Hybrid Gamma PXL function for pixel-precise display of greyscale and colour images with the appropriate gamma curve characteristics
- ✓ Uniform homogeneous display surface due to automatic control of luminance distribution (DUE)
- ✓ Prepared for calibration, acceptance and constancy testing according to local standards such as IPEM / AAPM Primary, DIN 6868-157 and QS-RL
- ✓ Effortless quality assurance and built-in calibration sensor
- ✓ Light sensor for measuring the ambient light within the reporting location
- ✓ Ergonomic design with fresh, clean aesthetics
- ✓ Compact dimensions and narrow housing frames
- ✓ 5-year warranty for highest investment security

Image quality

Precise, high-contrast, bright and crisp screen

Excellent image quality for the finest details

Thanks to the high 3 Megapixels (colour) resolution, a strong contrast ratio of 1800:1 and stable brightness of up to 1100 cd/m², the monitor offers excellent image quality. Even the differences between the finest details are shown – regardless of your viewing angle. This is a great advantage if multiple physicians are looking at the screen.




Observe monochrome and color images on a single monitor

The hybrid gamma PXL functionality automatically differentiates between monochrome and colour images, pixel by pixel. This creates a hybrid display on which each


pixel is displayed with the ideal tone value. In this way, a high level of precision and reliability is achieved.

The RX370 displays sophisticated monochrome images just as reliably as color images from various modalities. In practice, this means a significant increase in efficiency, as images from different imaging procedures can be displayed on just one monitor.




Blur reduction

LCD panels with a high brightness level tend to have more blurry image rendering thanks to over-framing than would be possible in comparison with an acquired exposure. Therefore, EIZO offers blur reduction anchored in monitor hardware. It retrieves details lost in the contours on the screen, meaning that the image is rendered as clearly as possible.



Sharpness recovery on



Sharpness recovery off

Consistent image quality thanks to integrated luminance sensor


The precise calibration of white point and tone value characteristic curve is provided by an integrated luminance sensor. This measures the brightness and grayscales and calibrates the monitor autonomously according to the DICOM® standard. The sensor works automatically, without restricting the field of vision of the monitor. You can save the costs, time, and effort of maintenance and rely on a consistently balanced image quality.



Illustration exemplary

Reliable brightness

EIZO is convinced of the quality of its products. The warranty for the monitors, therefore, also covers the brightness stability.



Uniform brightness and high color purity

The monitor shines thanks to its high color purity and uniform illumination. This is down to the Digital Uniformity Equalizer (DUE), which corrects imbalances automatically, pixel by pixel. Gray and color tones of radiological and other medical images are correctly rendered over the entire display. This is essential for precise image reproduction.




With DUE



Without DUE

Constant brightness during operation


A sensor for the backlight permanently determines the luminance of the monitor. The benefit: The defined and calibrated values are rendered exactly just seconds after the monitor is turned on and remain constant during the entire period of use. The sensor is invisibly integrated in the monitor.




Back of the monitor

One billion color tones thanks to 13 bit LUT

Color rendering is controlled by a 13 bit look-up table (LUT), up to 10 bits of which are available in the Display-Port connection. This produces a resolution with a maximum of 1 billion color tones. The rendering characteristic and fine structures required for diagnostics can therefore be precisely identified.



With 13 bit LUT




Without 13 bit LUT

Software and ease of use Features for greater comfort

Consistently secure image quality

The optional EIZO RadiCS software to secure image quality enables extensive maintenance and testing of monitors and includes calibration, acceptance and constancy testing, and the archiving of all areas. If you are working on multiple stations, the use of the RadiNET Pro is recommended. This can be used to centrally control the calibration of all monitors, including data history. This saves you a significant amount of time and ensures consistently high image quality across the entire setup. The basic version RadiCS LE - without acceptance and constancy testing - is already included with the RadiForce monitors.

- [Learn more about RadiCS LE software \(included in the delivery\)](#)
- [Learn more about RadiCS software \(optionally available\)](#)
- [Learn more about RadiNet Pro software \(optionally available\)](#)



The Work-and-Flow technology

With the increasing digitisation of modalities, radiologists are confronted with a growing amount of information on their screens. EIZO's unique work-and-flow technology, with new features designed to meet the needs of radiologists, effectively counters the complexity of data. The RadiForce RX370 and RadiCS-LE software solution enable you to benefit from the Work-and-Flow functions.

[More information about the Work-and-Flow functions](#)

Point-and-Focus: all eyes on the analysis

The Point-and-Focus function allows you to select and focus on relevant image areas quickly using your mouse or keyboard. By adjusting the brightness and greyscale, the interesting parts of an image are highlighted by dimming the surrounding areas.

Hide-and-Seek: fast retrieval of information

Hide-and-Seek adds the benefit of making it possible to access reports, patient files and other information on the display quickly and efficiently without needing an additional monitor. When you move your cursor towards or away from the edge of the screen, a PinP window hides and displays information.

Switch-and-Go: just one keyboard and mouse for two systems

Switch-and-Go makes it possible to work using just one keyboard and mouse at diagnostic imaging stations that make use of two computers. You can switch between the two systems simply by moving your cursor from one screen to the other. This ensures greater work efficiency and allows you to maintain a clear overview of your workstation.

Instant-Backlight-Booster: Higher brightness for better differentiability

The Instant Backlight Booster feature temporarily increases the brightness of the monitor for faster recognition of detailed medical images. With a single hotkey, users can activate the function for multiple monitors simultaneously, allowing them to easily view multiple screens

under the same high brightness conditions. The brightness automatically returns to the original setting after a short time so the screen can continue to be used under typical diagnostic conditions.

DICOM® Part 14 is not supported while Instant Backlight Booster is on.

Improved comfort Efficiency in diagnostics

Perfectly designed for diagnostic use


Narrow black frontal bezels make this device ideal for use in dark environments. They make it easy to visually concentrate on the display. Meanwhile, a white bezel at the sides of the monitors creates a fresh, clean look.




DAISY CHAIN METHOD

Efficient multi-display solution

Thanks to the signal input and output, you can link several RadiForce monitors through their DisplayPort interface. This means that you can realise multi-monitor solutions with the greatest of ease – without labourious and excessive cabling.



Daisy chain method



Conventional solution

RadiLight: Eye-friendly comfort light

EIZO offers a brand-new, easy-to-operate comfort light for radiologists who work in dark diagnosis rooms. The soft illuminance in the background of the screen reduces the strain on the eyes that frequently occurs due to constant light-dark changes between bright screens and objects in a dark environment.



Sustainability

Environmentally and socially conscious production

Environmentally friendly packaging

For the packaging of the RX370, EIZO uses a padding made of moulded pulp cellulose. The material is made from recycled cardboard and paper and has a much lower environmental impact when disposed of than traditional polystyrene or plastic. All cables are stored in a cardboard compartment instead of being individually packed in plastic bags.



Left: conventional packaging / Right: environmentally friendly materials

Socially responsible production

The RX370 is produced in a socially responsible way. It is free of child labour and forced labour. Suppliers along the supply chain have been carefully selected and they have also committed themselves to produce in a socially responsible way. This applies in particular to conflict minerals. We present a detailed report about our social responsibility annually and voluntarily.



Environmentally and climate friendly

Each RX370 is manufactured in our own factory, which implements an environmental and energy management system in accordance with ISO 14001 und ISO 50001. This includes measures to reduce waste, wastewater and emissions, resource and energy consumption, as well as to encourage environmentally conscious behavior among employees. We publicly report on these measures on an annual basis.



Sustainable and durable

The RX370 is designed to have a long service life and normally outlasts the warranty period by some distance. Replacement parts are available many years after production has ceased. The entire lifecycle takes into account the impact on the environment as the longevity of the product and the fact it can be repaired saves resources and protects the environment. When designing the RX370, we took a minimalistic approach to our resources by using high-quality components and materials, as well as a careful production process.



Warranty

Highest investment security

Five-year warranty

EIZO grants a five-year warranty. This is possible thanks to the highly developed production process based on a simple principle of success: sophisticated and innovative technology, made from high-end materials.



Graphics board recommendation

For precise diagnostics

EIZO Graphics card MED-XN63

The EIZO graphics card supports the properties, functions, and settings of the RadiForce RX370 optimally. It enables precise diagnosis and can control several monitors simultaneously. EIZO offers technical support and warranty service for the graphics card.

[To the graphics card overview](#)



Technical Data

GENERAL	
Item no.	RX370
Case color	Bicolor, black and white
Areas of application	Healthcare
Product line	RadiForce
Areas of application	Projection radiography, Computed tomography/MR imagine, Nuclear medicine and radiotherapy, Non-destructive-testing
EAN	4995047057994
SCREEN	
Screen size [in inches]	21,3
Screen size [in cm]	54,1
Format	3:4
Viewable image size (width x height) [in mm]	324,9 x 433,2
Resolution in MP	3 Megapixels (colour)
Ideal and recommended resolution	1536 x 2048
Pixel pitch [in mm]	0,2115 x 0,2115
Panel technology	IPS
Max. viewing angle horizontal	178
Max. viewing angle vertical	178
Number of colors or greyscale	1.07 billion colors (DisplayPort, 10 Bit), 16.7 million colors (DisplayPort, 8 Bit)
Color palette/look-up table	543 billion colour tones / 13 bit
Max. brightness (typical) [in cd/m ²]	1100
Recommended brightness [in cd/m ²]	500
Max. dark room contrast (typical)	1800:1
Response time black/white/black change (typical)	25
Backlight	LED
FEATURES & OPERATION	
Preset color/greyscale modes	2x manual memory locations, Text, sRGB, DICOM
DICOM tone curve	✓
Hardware calibration of brightness and light density characteristic curve	✓
Digital Uniformity Equalizer (homogeneity correction)	✓
Blur reduction	✓
Sensors	Ambient Light Sensor, Integrated luminance sensor, Backlight Sensor
On-screen menu languages	de, en, fr, es, it, se
Adjustment options	DICOM tonal value, Brightness, Gamma, Color saturation, Resolution, Scaling, OSD language, Blur reduction
Button Guide	✓
Integrated power unit	✓
CONNECTIONS	
Signal inputs	2x DisplayPort (HDCP 1.3), DVI-D (HDCP 1.4)
Signal outputs	1x DisplayPort (HDCP 1.2)
Daisy-chain capable	✓
USB specification	USB 2
USB upstream ports	2 x type B
USB downstream ports	1 x type C (15 W charging function), 2x type A
Graphic signal	DVI Single Link (TMDS), DisplayPort
ELECTRICAL DATA	
Frequency	Digital: 31-127 kHz/29-61,5 Hz; Sync Mode: 29,5-30,5 Hz/59-61 Hz
Power consumption (typical) [in watts]	36
Maximum Power Consumption [in watts]	105 (at maximum brightness with all signal inputs and USB ports in use)
Max. Power consumption in stand-by mode [in watts]	1
Power consumption with power switch off [in watts]	0
Power supply	AC 100-240V, 50/60Hz
Max. USB-C Power Delivery [in Watt]	15
DIMENSIONS & WEIGHT	
Dimensions (incl. stand) (width x height x depth) [in mm]	341,3 x 481,5-571,5 x 200
Weight (incl. stand) [in kg]	8
Weight (without stand) [in kg]	5.2
Dimension drawing (PDF)	Dimension drawing (PDF)
Rotatability of the stand [in °]	70
Tiltability forwards/backwards [in °]	5 / 30
Pivot between portrait / landscape	anti-clockwise
Height adjustment range [in mm]	90
Hole spacing	100 x 100
CERTIFICATION & STANDARDS	
Certification	CE (Medical Device), ANSI/AAMI ES60601-1, CSA C22.2 Nr. 601-1, IEC60601-1, UKCA, RCM, FCC-B, CAN ICES-3 (B), VCCI-B, RoHS, WEEE, China RoHS, CCC, EAC
SOFTWARE & ACCESSORIES	
Accompanying software and other accessories are available for download	RadiCS LE
Other box contents	2x Signal cable DisplayPort - DisplayPort, 2x USB cable (Type A - Type B), Manual via download, Power cord
Accessories	RadiNET Pro, RadiCS (UX2-Kit), RadiLight, MED-XN63
Recommended graphics card	MED-XN63

WARRANTY

Warranty periode	5 years
Included warranty	The warranty additionally covers normal wear and tear of the backlight when operated at a recommended maximum brightness of 500 cd/sqm and a white point of 7,500 K. EIZO guarantees this brightness for a period of 5 years from the date of purchase or for 20,000 hours of operation, whichever comes first. With a maximum brightness of 400 cd/sqm, the number of operating hours increases to 30,000.



**Experience the
RX370 in AR now!**