



[→ Product Website](#)

The S1934 with a resolution of 1280 x 1024 pixels and a maximum brightness of 250 cd/m² is particularly well suited for universal use in a professional context. The display backlight with efficient but bright white LEDs is a particularly impressive feature. The S1934 consumes just 9 watts in regular use. With its DisplayPort, DVI-D, D-Sub interfaces, the S1934 is equally adept at processing analogue and digital signals. Speakers and headphone jack are integrated into the housing. The monitor uses an automatic brightness control to set itself to match the ambient light.

- ✓ Contrast 1000:1, brightness 250 cd/sq m
- ✓ Energy-saving LED backlight, mercury-free
- ✓ Auto-EcoView and EcoView Index for maximum energy-saving and optimal ergonomics.
- ✓ Built-in speaker and headphone connection
- ✓ DisplayPort, DVI-D and D-sub inputs for digital and analogue connection
- ✓ 5-year warranty for highest investment security

Technical Data

GENERAL

| | |
|------------------------------|---|
| Item no. | S1934H-BK S1934H-GY |
| Case color | Black Light gray |
| Areas of application | Office |
| Product line | FlexScan |
| Areas of application | Large and medium-sized companies, Private user & small business, Finance, Control rooms |
| Specific system requirements | None, compatible with most computers and operating systems including macOS and Windows |
| EAN | 4995047049234 4995047049227 |

SCREEN

| | |
|---|--|
| Screen size [in inches] | 19 |
| Screen size [in cm] | 48 |
| Format | 5:4 |
| Viewable image size (width x height) [in mm] | 375 x 300 |
| Ideal and recommended resolution | 1280 x 1024 |
| Pixel pitch [in mm] | 0,29 x 0,29 |
| Supported resolutions | 1280 x 1024, 1024 x 768, 800 x 600, 720 x 400, 640 x 480 |
| Panel technology | IPS |
| Max. viewing angle horizontal | 178 |
| Max. viewing angle vertical | 178 |
| Number of colors or greyscale | 16,7 million colors (D-Sub, 8 Bit), 16,7 million colors (DVI, 8 Bit), 16,7 million colors (DisplayPort, 8 Bit) |
| Color palette/look-up table | 1.06 billion color tones / 10 Bit |
| Max. color space (typical) | sRGB (100%) |
| Max. brightness (typical) [in cd/m ²] | 250 |
| Max. dark room contrast (typical) | 1000:1 |
| Response time grey-grey alternation (typical) [in ms] | 14 |
| Backlight | LED |

FEATURES & OPERATION

| | |
|------------------------------------|--|
| Preset color/greyscale modes | 2x manual memory locations, sRGB, Paper, DICOM |
| Auto EcoView | ✓ |
| EcoView Index | ✓ |
| HDCP Decoder | ✓ |
| Automatic signal input recognition | ✓ |
| Built-in speakers | ✓ |
| On-screen menu languages | de, en, fr, es, it, se |
| Adjustment options | Color Mode, Brightness, Contrast, Color temperature /White point, Gamma, Colour tone, Color saturation, Resolution, Scaling, OSD language, Signal input, All EcoView functions, Volume |
| Integrated power unit | ✓ |

CONNECTIONS

| | |
|--------------------------|---|
| Signal inputs | D-Sub, DisplayPort (HDCP 1.3), DVI-D (HDCP 1.4) |
| Graphic signal | DVI Single Link (TMDS), RGB Analog, DisplayPort |
| Sync formats | Separate |
| Audio input | 3,5 mm stereo jack, DisplayPort |
| Audio / headphone output | 3.5 mm stereo jack |

ELECTRICAL DATA

| | |
|--|--|
| Frequency | DVI-D: 31-64 kHz/59-61 Hz; D-Sub: 31-64 kHz/55-61 Hz |
| Power consumption (typical) [in watts] | 9 |
| Maximum Power Consumption [in watts] | 21 (at maximum brightness with all signal inputs and USB ports in use) |
| Max. Power consumption in stand-by mode [in watts] | 0.5 |
| Power consumption with power switch off [in watts] | 0 |
| Energy efficiency class | C |
| Energy consumption/1000h [in kWh] | 9 |
| Power supply | AC 100-120 V / 200-240 V, 50/60 Hz |

DIMENSIONS & WEIGHT

| | |
|---|---|
| Dimensions (incl. stand) (width x height x depth) [in mm] | 405 x 407-507 x 205 |
| Weight (incl. stand) [in kg] | 5.6 |
| Dimensions (without stand) (width x height x depth) [in mm] | 405 x 334 x 62 |
| Weight (without stand) [in kg] | 3.8 |
| Dimension drawing (PDF) | Dimension drawing (PDF) |
| Rotatability of the stand [in °] | 35 |
| Tiltability forwards/backwards [in °] | 0 / 30 |
| Pivot between portrait / landscape | clockwise |
| Height adjustment range [in mm] | 100 |
| Hole spacing | 100 x 100 |

CERTIFICATION & STANDARDS

| | |
|---------------|---|
| Certification | CE, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), EPEAT 2018 (US), RCM, cTÜVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA ENERGY STAR, RoHS, WEEE, China RoHS, CCC, EAC |
|---------------|---|

SOFTWARE & ACCESSORIES

| | |
|--------------------|--|
| Other box contents | Signal cable DVI-D - DVI-D, Manual via download, Power cord, Quick guide |
|--------------------|--|

WARRANTY

| | |
|------------------|--|
| Warranty periode | 5 years for unit and LCD module up to 30,000 operating hours, whichever comes first. |
| Warranty type | Swiss Edition Warranty |



FlexScan **S1934**

Find your EIZO contact:
EIZO AG - Switzerland
Moosacherstrasse 6, Au
8820 Wädenswil ZH
Phone +41 44 782 24 40
www.eizo.ch

All product names are trademarks or registered trademarks of EIZO Corporation in Japan and other countries or their respective companies. Copyright © 2024 EIZO Europe GmbH, Belgrader Str. 2, 41069 Mönchengladbach, Germany. All rights, errors and modifications reserved. Latest update: 21.04.2024